



Stator lengths available:

Model	Length (in)	mm	Cont. Watts
507	1.2	30mm	50

12mm OD 500 Series (Proton) brushless motors operate in the 50 to 100 watt range. 500 series motors excel at high RPM (80,000 RPM max) applications.

Applications have included miniature swarming UAV drives.

Motor type: inrunner	Finned: Optional	Gearbox(es): P16
Poles: 4p	Sealed: No	Shaft size(s): 1.5 or 2mm
Slots: 6s	Sensored: Optional	Max RPM: 100,000

507	Diam.	Length	Weight	Max Cont. Watts	Max Peak Watts
	inch: 0.5	1.2	.5 ozs.	50	100
	mm: 13	30	14g		

Motor	KV	Rm Ohms	Io @ 10v	Torque Constant mNm/A inOz/A	Max Volts	Max Amps
507	3,200	0.500	0.2	2.990 0.423	31	3
507	4,000	0.300	0.3	2.392 0.339	25	4
507	5,300	0.180	0.4	1.805 0.256	19	5

507	Diam.	Length	Weight	Max Cont. Watts	Max Peak Watts
	inch: 0.5	1.2	.5 ozs.	50	100
	mm: 13	30	14g		

Motor	KV	Rm Ohms	Io @ 10v	Torque Constant		Max Volts	Max Amps
				mNm/A	inOz/A		
507	7,300	0.099	0.7	1.311	0.186	14	7
507	8,300	0.090	0.8	1.153	0.163	12	8
507	11,000	0.050	1.4	0.870	0.123	9	11

NEUTRONICS ENTERPRISES INC.
4631 Viewridge Ave Unit B
San Diego, CA 92123

email: info@neutronics.com
phone: 858-674-2250

<http://www.neumotors.com>

DOMESTIC CONTENT / COUNTRY OF ORIGIN

Motors may be assembled with varying degrees of domestic (USA) content. Please contact to discuss content requirements, solutions, and resulting pricing variances, if any. Baseline motors are assembled and or tested in the US or Mexico from components sourced globally, including China.

QUALITY CONTROL

Our factory is ISO 9001 certified. Quality documentation available on a custom order basis.

POWER RATINGS (Watts):

Continuous rating is the power the motor can deliver while maintaining the external housing temperatures below 100C.

MAX power rating is the power the motor can deliver beginning with motor at a temp of 20C until it reaches it's limit temperature of 100C. The exact maximum power output of a motor is dependent on a number of variables including air flow, ambient air temperature, contact cooling, etc. 100C rating is measured on the outside of the case, which allows for higher internal temperatures and a small measure of overhead.

MAX VOLTAGE

Limited by kv (RPMs per volt) times the applied voltage. Max voltage must be kept below the voltage which will spin the motor over max rpm for the motor series.

MAX AMPERAGE

See power ratings above.

MTBF RATINGS:

When used within the constraints described above, BLDC motors' primary "wear" item(s) are the bearings supporting the shaft. Bearing life is inversely affected by speed, temperature, radial and axial loads. While an MTBF figure can be generated, it would be rendered invalid by excursions beyond prescribed temperatures or load limits – such as prop strikes or side loads. MTBF must be determined on a case by case basis, and even then it would be subject to numerous exceptions.

COMPONENT SPECIFICATIONS

Winding temperature: 180C
Magnet grade: 180C UH grade
Bearings: Japanese SPB bearings

Specifications subject to change without notice.

Copyright (c) 2021 Neutronics Enterprises Inc.